

IN THE CLAIMS:

Please amend claims 1, 12, 16, 22, 55, 66, and 77, as indicated by the complete listing of claims provided below.

- C
1. (currently amended) A method for accessing a broad data field having fine resolution comprising:  
selecting a scale to control a range for accessing data within the data field, the scale being ~~under control of~~ depicted by a first control element of a graphical user interface;  
moving the range to encompass different portions of the data field, a position of the range relative to the data field being ~~under control of~~ depicted by a second control element of the graphical user interface; and  
changing simultaneously the scale while moving the range over different portions of the data field.
  2. (original) The method as defined by Claim 1 wherein the scale is controlled by moving a cursor positioning device along a first axis.
  3. (previously presented) The method as defined by Claim 2 wherein the position of the range is controlled by moving the cursor positioning device along a second axis.
  4. (previously presented) The method as defined by Claim 2 wherein the position of the range is controlled by moving the cursor positioning device in an axis orthogonal to the first axis.

- C\
5. The method as defined by Claim 4 wherein moving the cursor positioning device in an upward motion increases the scale and moving the cursor positioning device in a downward motion decreases the scale.
  6. (previously presented) The method as defined by Claim 5 wherein moving the cursor positioning device to the right causes the range to be shifted to the right and moving the cursor positioning device to the left causes the range to be shifted to the left.
  7. (previously presented) The method as defined by Claim 6 wherein a particular piece of data can be accessed within the data field having five orders of magnitude.
  8. (original) The method as defined by Claim 7 wherein the range is depicted by a timeline.
  9. (previously presented) The method as defined by Claim 8 wherein the cursor positioning device is also capable of controlling the position of a cursor of the graphical user interface on a display screen.
  10. (previously presented) The method as defined by Claim 9 wherein the scale and the position of the range are capable of being simultaneously controlled by the cursor positioning device after positioning the cursor over an icon and depressing a button.
  11. (previously presented) The method as defined by Claim 10 wherein the cursor positioning device is at least one of a mouse, a track ball, a touch tablet, joystick.

- C
12. (currently amended) A method for accessing a particular piece of data within a broad data field having fine resolution comprising:
- selectively varying a scale, thereby determining a range, the range spanning a portion of the data field, the scale being ~~under control of~~ depicted by a first control element of a graphical user interface;
  - moving the range relative to the data field, thereby encompassing portions of the data field such that the particular piece of data lies within the range, a position of the range relative to the data field being ~~under control of~~ depicted by a second control element of the graphical user interface;
  - locating a point close to the location of the particular piece of data within the data field using the second control element;
  - decreasing the scale, thereby increasing the range's resolution, while simultaneously moving the range relative to the data field to keep the point within the range;
  - and
  - successively repeating said decreasing and said locating, until the particular piece of data is actually accessed.
13. (previously presented) The method as defined by Claim 12 wherein the scale is controlled by moving a mouse along an axis and the position of the range is controlled by moving the mouse along another axis.
14. (previously presented) The method as defined by Claim 13 wherein the mouse is also capable of controlling the position of a cursor of the graphical user interface on a display screen.

15. (previously presented) The method as defined by Claim 12 wherein the scale is controlled by moving a trackball along an axis and the position of the range is controlled by moving the trackball along another axis.
16. (currently amended) An apparatus for accessing a broad data field having fine resolution comprising:  
a means for selecting a scale for controlling a range within the data field, the scale being ~~under control of~~ depicted by a first control element of a graphical user interface;  
a means for moving the range to encompass different portions of the data field, a position of the range relative to the data field being ~~under control of~~ depicted by a second control element of the graphical user interface; and  
a means for simultaneously selecting the scale while moving the range over different portions of the data field.
17. (canceled)
18. (previously presented) The apparatus as defined by Claim 16 including a switching means for switching a mouse between controlling a cursor's position on a display screen and controlling the scale and the position of the range.
19. (previously presented) The apparatus as defined by Claim 18 wherein the scale is controlled by moving the mouse along an axis and the position of the range is controlled by moving the mouse along another axis.

C

20. (canceled)

21. (previously presented) The apparatus as defined by Claim 19 wherein the range is depicted as a timeline.

22. (currently amended) A method for accessing a data set containing a plurality of items comprising:

selecting a scale of access to the data set according to input from an input device with relation to a first axis of a first degree of freedom of the input device, the scale being ~~under control of~~ depicted by a first control element of a graphical user interface; and

selecting a position of access to the data set at the scale according to input from the input device with relation to a second axis of a second degree of freedom of the input device while the first degree of freedom of the input device controls said selecting the scale in the first graphical user interface element, the position being ~~under control of~~ depicted by a second control element of the graphical user interface.

23. (original) The method as defined by Claim 22 wherein the input device is at least one of a mouse, a track ball, a touch tablet, a joystick.

24. (previously presented) The method as defined by Claim 23 wherein the first and the second axes of the input device are capable of being remapped such that the input

device controls positioning a cursor of the graphical user interface on a display screen.

25. (previously presented) A method for accessing a particular piece of data within a broad data field having fine resolution comprising:

selecting a scale wherein the particular piece of data lies within a range which encompasses a continuous portion of the data set, the scale depicting a magnification level of the data field, the scale being controlled by a first degree of freedom of an input device in a first control element of a graphical user interface;

decreasing the scale such that the magnification level is increased;

changing a span of the data field covered by the range, according to the scale selected;

moving the data field such that the particular piece of data falls within the range, said moving controlled by a second degree of freedom of the input device in a second control element of the graphical user interface while the first degree of freedom of the input device controls the first control element; and

successively repeating said decreasing the scale and said moving the data field, until the particular piece of data is actually accessed.

26. (previously presented) A method for accessing a data field in a data processing system, the method comprising:

when the data processing system is in a first mode:

positioning a cursor to locations on a display screen in response to movement of an input device;

receiving a signal to enter into a second mode;  
when the data processing system is in the second mode:  
remapping control of the input device to control both a scale and a position,  
the scale and the position specifying a portion of the data field for  
access;  
adjusting the scale according to movement of the input device along a first  
axis; and  
adjusting the position according to movement of the input device along a  
second axis.

2 27. (previously presented) A method as in claim 26 wherein in the second mode:  
the scale is increased when the input device moves in an upward motion; and  
the scale is decreased when the input device moves in a downward motion.

C 3 28. (previously presented) A method as in claim 27 wherein in the second mode:  
a later portion of the data field is selected when the input device moves to the right;  
and  
an earlier portion of the data field is selected when the input device moves to the left.

4 29. (previously presented) A method as in claim 28 wherein, to enter into the second  
mode, the signal is received when the cursor is over an icon and when a switch is  
activated.

5 30. (previously presented) A method as in claim 29 wherein the input device includes one  
of:

- a) a mouse;
- b) a track ball;
- c) a touch tablet; and
- d) a joystick.

6  
31.

(previously presented) A method as in claim 26 further comprising:

receiving input of moving simultaneously the input device in the first and second axes  
to simultaneously adjust the scale and the position when in the second mode.

7  
32.

(previously presented) A method as in claim 31 wherein the input device is comprised  
of a mouse and the scale is controlled by moving the mouse in the first axis and the  
position is controlled by moving the mouse in the second axis.

8  
33.

(previously presented) A method as in claim 31 wherein the input device is comprised  
of a track ball and the scale is controlled by moving the track ball in the first axis and  
the position is controlled by moving the track ball in the second axis.

9  
34.

(previously presented) A machine readable medium containing executable computer  
program instructions which when executed by a data processing system cause said  
system to perform a method for accessing a data field in the data processing system,  
the method comprising:

when the data processing system is in a first mode:

positioning a cursor to locations on a display screen in response to movement  
of an input device;

receiving a signal to enter into a second mode;



when the data processing system is in the second mode:

remapping control of the input device to control both a scale and a position,

the scale and the position specifying a portion of the data field for

access;

adjusting the scale according to movement of the input device along a first

axis; and

adjusting the position according to movement of the input device along a

second axis.

10  
35.

(previously presented) A medium as in claim <sup>9</sup>34 wherein in the second mode:  
the scale is increased when the input device moves in an upward motion; and  
the scale is decreased when the input device moves in a downward motion.

11  
36.

(previously presented) A medium as in claim <sup>10</sup>35 wherein in the second mode:  
a later portion of the data field is selected when the input device moves to the right;  
and  
an earlier portion of the data field is selected when the input device moves to the left.

12  
37.

(previously presented) A medium as in claim <sup>11</sup>36 wherein, to enter into the second  
mode, the signal is received when the cursor is over an icon and when a switch is  
activated.

13  
38.

(previously presented) A medium as in claim <sup>12</sup>37 wherein the input device includes  
one of:  
a) a mouse;

- b) a track ball;
- c) a touch tablet; and
- d) a joystick.

14/  
39.

(previously presented) A medium as in claim 9/  
34 wherein the method further comprises:

receiving input of moving simultaneously the input device in the first and second axes  
to simultaneously adjust the scale and the position when in the second mode.

15/  
40.

(previously presented) A medium as in claim 14/  
39 wherein the input device is comprised of a mouse and the scale is controlled by moving the mouse in the first axis and the position is controlled by moving the mouse in the second axis.

16/  
41.

(previously presented) A medium as in claim 14/  
39 wherein the input device is comprised of a track ball and the scale is controlled by moving the track ball in the first axis and the position is controlled by moving the track ball in the second axis.

17/  
42.

(previously presented) A data processing system to control access to a data field, the system comprising:

means for positioning a cursor to locations on a display screen in response to  
movement of an input device when the data processing system is in a first  
mode;

means for receiving a signal to enter into a second mode;

means for remapping control of the input device to control both a scale and a position  
when the data processing system is in the second mode, the scale and the  
position specifying a portion of the data field for access;  
means for adjusting the scale according to movement of the input device along a first  
axis when in the second mode; and  
means for adjusting the position according to movement of the input device along a  
second axis when in the second mode.

18/  
43.

(previously presented) A processing system as in claim 42<sup>17/</sup> wherein in the second mode:

the scale is increased when the input device moves in an upward motion; and  
the scale is decreased when the input device moves in a downward motion.

19/  
44.

(previously presented) A processing system as in claim 43<sup>18/</sup> wherein in the second mode:

a later portion of the data field is selected when the input device moves to the right;  
and

an earlier portion of the data field is selected when the input device moves to the left.

20/  
45.

(previously presented) A processing system as in claim 44<sup>19/</sup> wherein, to enter into the second mode, the signal is received when the cursor is over an icon and when a switch is activated.

21/  
46.

(previously presented) A processing system as in claim 45<sup>20/</sup> wherein the input device includes one of:

- a) a mouse;
- b) a track ball;
- c) a touch tablet; and
- d) a joystick.

22/  
47.

(previously presented) A processing system as in claim ~~42~~ further comprising:  
means for receiving input of moving simultaneously the input device in the first and  
second axes to simultaneously adjust the scale and the position when in the  
second mode.

23/  
48.

(previously presented) A processing system as in claim ~~47~~ wherein the input device is  
comprised of a mouse and the scale is controlled by moving the mouse in the first  
axis and the position is controlled by moving the mouse in the second axis.

24/  
49.

(previously presented) A processing system as in claim ~~47~~ wherein the input device is  
comprised of a track ball and the scale is controlled by moving the track ball in the  
first axis and the position is controlled by moving the track ball in the second axis.

50.

(withdrawn) A method to control a graphical user interface, the method comprising:  
receiving a first input which indicates a movement of an input device in a first degree  
of freedom of the input device while a cursor of the graphical user interface is  
outside a first region; and  
adjusting a first parameter under control of a first user interface element of the  
graphical user interface according to the first input, the first user interface  
element being located within the first region.

C

- C\
51. (withdrawn) A method as in claim 50 wherein the first user interface element is controllable by a movement of the input device when the cursor of the graphical user interface is within the first region.
52. (withdrawn) A method as in claim 50 further comprising:  
receiving a second input which indicates a movement of the input device in a second degree of freedom of the input device; and  
adjusting a second parameter under control of a second user interface element of the graphical user interface according to the second input, the second user interface element being located within a second region, the second region being outside the first region.
53. (withdrawn) A method as in claim 52 wherein the first user interface element is controllable by a movement of the input device when the cursor of the graphical user interface is within the first region; and, wherein the second user interface element is controllable by a movement of the input device when the cursor of the graphical user interface is within the second region.
54. (withdrawn) A method as in claim 53 wherein the first user interface element comprises a slider and the second user interface element comprises a timeline.
55. (currently amended) A method to control a graphical user interface, the method comprising:  
receiving a first input which indicates a first movement of an input device, the first input comprising:

a first component which indicates a component of the first movement  
according to a first degree of freedom of the input device, and  
a second component which indicates a component of the first movement  
according to a second degree of freedom of the input device;  
adjusting a first parameter ~~under control of~~ depicted by a first user interface element  
of the graphical user interface according to the first component, the first user  
interface element being located in a first region in the graphical user interface;  
and  
adjusting a second parameter ~~under control of~~ depicted by a second user interface  
element of the graphical user interface according to the second component, the  
second user interface element being located in a second region in the graphical  
user interface.

- C\
56. (previously presented) A method as in claim 55 wherein the first user interface element is controllable by the input device when a cursor of the graphical user interface is in the first region; and, the second user interface element is controllable by the input device when the cursor of the graphical user interface is in the second region.
57. (previously presented) A method as in claim 56 wherein the first and second regions are not overlapping with each other.
58. (previously presented) A method as in claim 57 wherein the cursor is not displayed when the first parameter is adjusted according to the first component and the second parameter is adjusted according to the second component.

59. (previously presented) A method as in claim 55 wherein the first and second parameters are independent from each other.
60. (previously presented) A method as in claim 55 further comprising:  
determining a dominant one of the first component and the second component;  
wherein only one of the first and second parameters is adjusted according to the  
dominant one of the first component and the second component.
61. (withdrawn) A machine readable medium containing executable computer program instructions which when executed by a data processing system cause said system to perform a method to control a graphical user interface on the data processing system, the method comprising:  
receiving a first input which indicates a movement of an input device in a first degree  
of freedom of the input device while a cursor of the graphical user interface is  
outside a first region; and  
adjusting a first parameter under control of a first user interface element of the  
graphical user interface according to the first input, the first user interface  
element being located within the first region.
62. (withdrawn) A medium as in claim 61 wherein the first user interface element is controllable by a movement of the input device when the cursor of the graphical user interface is within the first region.
63. (withdrawn) A medium as in claim 61 wherein the method further comprises:

receiving a second input which indicates a movement of the input device in a second degree of freedom of the input device; and  
adjusting a second parameter under control of a second user interface element of the graphical user interface according to the second input, the second user interface element being located within a second region, the second region being outside the first region.

- C\
64. (withdrawn) A medium as in claim 63 wherein the first user interface element is controllable by a movement of the input device when the cursor of the graphical user interface is within the first region; and, wherein the second user interface element is controllable by a movement of the input device when the cursor of the graphical user interface is within the second region.
65. (withdrawn) A medium as in claim 64 wherein the first user interface element comprises a slider and the second user interface element comprises a timeline.
66. (currently amended) A machine readable medium containing executable computer program instructions which when executed by a data processing system cause said system to perform a method to control a graphical user interface on the data processing system, the method comprising:  
receiving a first input which indicates a first movement of an input device, the first input comprising:  
a first component which indicates a component of the first movement according to a first degree of freedom of the input device, and
- C



a second component which indicates a component of the first movement  
according to a second degree of freedom of the input device;  
adjusting a first parameter ~~under control of~~ depicted by a first user interface element  
of the graphical user interface according to the first component, the first user  
interface element being located in a first region in the graphical user interface;  
and  
adjusting a second parameter ~~under control of~~ depicted by a second user interface  
element of the graphical user interface according to the second component, the  
second user interface element being located in a second region in the graphical  
user interface.

- C \
67. (previously presented) A medium as in claim 66 wherein the first user interface element is controllable by the input device when a cursor of the graphical user interface is in the first region; and, the second user interface element is controllable by the input device when the cursor of the graphical user interface is in the second region.
68. (previously presented) A medium as in claim 67 wherein the first and second regions are not overlapping with each other.
69. (previously presented) A medium as in claim 68 wherein the cursor is not displayed when the first parameter is adjusted according to the first component and the second parameter is adjusted according to the second component.

70. (previously presented) A medium as in claim 66 wherein the first and second parameters are independent from each other.
71. (previously presented) A medium as in claim 66 wherein the method further comprises:  
determining a dominant one of the first component and the second component;  
wherein only one of the first and second parameters is adjusted according to the dominant one of the first component and the second component.
72. (withdrawn) A data processing to control a graphical user interface, the data processing system comprising:  
means for receiving a first input which indicates a movement of an input device in a first degree of freedom of the input device while a cursor of the graphical user interface is outside a first region; and  
means for adjusting a first parameter under control of a first user interface element of the graphical user interface according to the first input, the first user interface element being located within the first region.
73. (withdrawn) A data processing system as in claim 72 wherein the first user interface element is controllable by a movement of the input device when the cursor of the graphical user interface is within the first region.
74. (withdrawn) A data processing system as in claim 72 further comprising:

means for receiving a second input which indicates a movement of the input device in a second degree of freedom of the input device; and  
means for adjusting a second parameter under control of a second user interface element of the graphical user interface according to the second input, the second user interface element being located within a second region, the second region being outside the first region.

75. (withdrawn) A data processing system as in claim 74 wherein the first user interface element is controllable by a movement of the input device when the cursor of the graphical user interface is within the first region; and, wherein the second user interface element is controllable by a movement of the input device when the cursor of the graphical user interface is within the second region.

76. (withdrawn) A data processing system as in claim 75 wherein the first user interface element comprises a slider and the second user interface element comprises a timeline.

77. (currently amended) A data processing to control a graphical user interface, the data processing system comprising:  
means for receiving a first input which indicates a first movement of an input device, the first input comprising:  
a first component which indicates a component of the first movement according to a first degree of freedom of the input device, and  
a second component which indicates a component of the first movement according to a second degree of freedom of the input device;

means for adjusting a first parameter ~~under control of~~ depicted by a first user interface element of the graphical user interface according to the first component, the first user interface element being located in a first region in the graphical user interface; and

means for adjusting a second parameter ~~under control of~~ depicted by a second user interface element of the graphical user interface according to the second component, the second user interface element being located in a second region in the graphical user interface.

- C\
78. (previously presented) A data processing system as in claim 77 wherein the first user interface element is controllable by the input device when a cursor of the graphical user interface is in the first region; and, the second user interface element is controllable by the input device when the cursor of the graphical user interface is in the second region.
79. (previously presented) A data processing system as in claim 78 wherein the first and second regions are not overlapping with each other.
80. (previously presented) A data processing system as in claim 79 wherein the cursor is not displayed when the first parameter is adjusted according to the first component and the second parameter is adjusted according to the second component.
81. (previously presented) A data processing system as in claim 77 wherein the first and second parameters are independent from each other.

C\

82. (previously presented) A data processing system as in claim 77 further comprising:  
means for determining a dominant one of the first component and the second  
component;  
wherein only one of the first and second parameters is adjusted according to the  
dominant one of the first component and the second component.

---